UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/635,436	08/07/2003	Alejandro Wiechers	200207414-1	8520
22879 7590 12/01/2008 HEWLETT PACKARD COMPANY P O BOX 272400, 3404 E. HARMONY ROAD INTELLECTUAL PROPERTY ADMINISTRATION			EXAMINER	
			SINGH, SATWANT K	
	NS, CO 80527-2400		ART UNIT	PAPER NUMBER
·			2625	
			NOTIFICATION DATE	DELIVERY MODE
			12/01/2008	ELECTRONIC

# Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

JERRY.SHORMA@HP.COM mkraft@hp.com ipa.mail@hp.com

	Application No.	Applicant(s)		
	10/635,436	WIECHERS, ALEJANDRO		
Office Action Summary	Examiner	Art Unit		
	SATWANT K. SINGH	2625		
The MAILING DATE of this communication ap Period for Reply	pears on the cover sheet with the c	correspondence address		
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING ID.  - Extensions of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory or Failure to reply within the set or extended period for reply will, by stature Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATION  .136(a). In no event, however, may a reply be tind  d will apply and will expire SIX (6) MONTHS from te, cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).		
Status				
Responsive to communication(s) filed on 28 / 2a) This action is <b>FINAL</b> . 2b) This 3) Since this application is in condition for allowed closed in accordance with the practice under	is action is non-final. ance except for formal matters, pro			
Disposition of Claims				
4)  Claim(s) 1-19 is/are pending in the application 4a) Of the above claim(s) is/are withdra 5)  Claim(s) is/are allowed.  6)  Claim(s) 1-19 is/are rejected.  7)  Claim(s) is/are objected to.  8)  Claim(s) are subject to restriction and/	awn from consideration.  For election requirement.			
<ul> <li>9) ☐ The specification is objected to by the Examin 10) ☐ The drawing(s) filed on <u>07 August 2003</u> is/are Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the Examination.</li> </ul>	: a) ☐ accepted or b) ☐ objected education of accepted or b) ☐ objected education of acceptance. See ction is required if the drawing(s) is objection is required if the drawing(s) is objection is required if the drawing(s) is objected or b) ☐	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).		
Priority under 35 U.S.C. § 119				
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>				
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (PTO-948)  3) Information Disclosure Statement(s) (PTO/SB/08)  Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal F 6) Other:	ate		

Art Unit: 2625

#### **DETAILED ACTION**

## Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 28 August 2008 has been entered.

# Response to Amendment

2. This office action is in response to the amendment filed on 28 August 2008.

# Response to Arguments

3. Applicant's arguments with respect to claims 1, 7, and 13 have been considered but are most in view of the new ground(s) of rejection.

## Claim Rejections - 35 USC § 103

- 4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 5. Claims 1-19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Stewart et al (US 6,714,964) in view of Hull et al. (US 2007/0253020), Warmus et al. (US 5,963,968) and Ryan et al. (US 7,206,087).

Application/Control Number: 10/635,436

Page 3

Art Unit: 2625

6. Regarding Claim 1, Stewart et al teach a method of managing workflow in a commercial printing environment including a designer location (client side of the network 300a) and a print service provider location (printer side 300c), said method comprising: creating a press ready file at the designer location (Fig. 7, S600-640) (user creates a document in a local application, creates a PDF file which is combined with the finishing and binding options to create a print ready file) (col. 8, lines 45-67, col. 9, lines 1-4) using the updated device information from the print service provider location (print driver selected by the user is verified) (col. 7, lines 42-67); submitting said press ready file to the print service provider location via an electronic network (print ready file is sent to the print queue and transferred to the production facility) (col. 8, lines 45-67, col. 9, lines 1-4).

Stewart et al fails to teach automatically pre-flighting a received document file, including automatically checking for common errors associated during a prepress stage, automatically revising incorrect printing instructions and automatically adding missing printing instructions to the received document file; and automatically providing a remote proofing function for a customer of the document file to be printed and automatically tracking the printing of the document file by continuously monitoring and updating a status of the document file to be printed.

Hull et al teaches automatically pre-flighting a received document file, including automatically checking for common errors associated during a prepress stage, automatically revising incorrect printing instructions and automatically adding missing printing instructions to the received document file; and automatically providing a remote

proofing function for a customer of the document file to be printed and automatically tracking the printing of the document file by continuously monitoring and updating a status of the document file to be printed ("soft-proofing" the job) (page 7, paragraph [0044]).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to have combined the teachings of Stewart with the teaching of Hull to allow a user to "soft-proof" a job to catch any errors in the print job prior to the final output in order to prevent wasting the print jobs resources by having to re-print the job if the errors are not corrected.

Stewart et al and Hull et fail to teach a method, verifying, at said print service provider location, that said press ready file will print at said print service provider location as designed at the designer location and, if not, correcting said press ready file to ensure printing substantially as designed; and performing automated shipping using, if created, said corrected press ready file, else using said verified press ready file.

Warmus et al teach a method, verifying, at said print service provider location, that said press ready file will print at said print service provider location as designed at the designer location and, if not, correcting said press ready file to ensure printing substantially as designed (control unit to control and makeready files and cause one or more demand printing system to print desired pages) (col. 5, lines 44-59); and performing automated shipping using, if created, said corrected press ready file, else using said verified press ready file (printed pages printed by the demand printing system supplied to a finishing apparatus) (col. 5, lines 60-67, col. 6, lines 1-8).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to have combined the teachings of Stewart and Hull with the teaching of Warmus to provide the necessary verification needed to insure the correct output is shipped.

Stewart et al, Hull et al, and Warmus et al fail to teach a method comprising: establishing a link to the print service provider location from the designer location and obtaining updated device information including functional capabilities of a desired printing device and at least one production device; and verifying that required elements for completion of a production of a print lob at the print service provider location are present in the print job based on the updated device information.

Ryan et al teaches a method comprising: establishing a link to the print service provider location from the designer location and obtaining updated device information including functional capabilities of a desired printing device and at least one production device (Fig. 10 Steps 101) (a table of printer capabilities and constraints is retrieved form the VJTDB and a table of finisher/assembler capabilities and constraints is retrieved form the VJTDB) (col. 18, lines 43-52); and verifying that required elements for completion of a production of a print lob at the print service provider location are present in the print job based on the updated device information (Fig. 10 Step 103) (PMC using the retrieved lists of all of the capabilities and constraints of the devices described in the VJTDB to generate a list of all possible specific paths or threads, by which the retrieved devices can implement the operations and attributes identified in the job model) (col. 18, lines 57-67).

Application/Control Number: 10/635,436

Art Unit: 2625

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to have combined the teachings of Stewart, Hull, and Warmus with the teaching of Ryan to verify that the printer is capable of outputting the print job prior to submitting the print job to the particular printer.

Page 6

- 7. Regarding claim 2, Stewart et al teach a method, wherein said step of creating a press ready file at the designer location further comprises performing automated remote shipping setup of said press ready file to remotely select the desired shipping options for said press ready file when printed at said print service provider location (servicing on the completed jobs includes shipping or delivery of the documents) (col. 8, lines 39-44).
- 8. Regarding Claim 3, Stewart et al teach a method, wherein said step of verifying, at said print service provider location, further comprises performing automated remote shipping setup (servicing on the completed jobs includes shipping or delivery of the documents) (col. 8, lines 39-44).
- 9. Regarding Claim 4, Stewart et al teach a method, wherein said step of automated shipping is performed and wherein an automated shipping device is used to ship said printed output in accordance with shipping instructions in said press ready file (Fig. 7C, S670 and S675, package shrink wrapped and sent for delivery) (col. 9, lines 1-4).
- 10. Regarding Claim 5, Stewart et al disclose a method, wherein said step of correcting includes reading shipping instructions prepared at the designer location and preparing appropriate corresponding instructions for an actual shipping device to be

used at the print service provider location (Fig. 7C, S670 and S675, package shrink wrapped and sent for delivery) (col. 9, lines 1-4).

- 11. Regarding Claim 6, Stewart et al teach a method, wherein said step of correcting further comprising updating a job ticket corresponding to said press ready file (Fig. 7B, S650 and Fig. 7C, S655, print ready file is transferred to the production facility and queued to an available printer) (col. 8, lines 62-67, col. 9, lines 1-4).
- 12. Regarding Claim 7, Stewart et al teach a computer readable medium encoded with a program product for managing workflow in a commercial printing environment including a designer location (client side of the network 300a) and a print service provider location (printer side 300c), said product comprising machine-readable program code for causing, when executed, a machine to perform the following method steps: creating a press ready file at the designer location (Fig. 7, S600-640) (user creates a document in a local application, creates a PDF file which is combined with the finishing and binding options to create a print ready file) (col. 8, lines 45-67, col. 9, lines 1-4) using updated device configuration information from the print service provider location (print driver selected by the user is verified) (col. 7, lines 42-67); submitting said press ready file to the print service provider location via an electronic network (print ready file is sent to the print queue and transferred to the production facility) (col. 8, lines 45-67, col. 9, lines 1-4).

Stewart et al fail to teach a computer readable medium encoded with a program product, automatically pre-flighting a received document file, including automatically checking for common errors associated during a prepress stage, automatically revising

incorrect printing instructions and automatically adding missing printing instructions to the received document file; and automatically providing a remote proofing function for a customer of the document file to be printed and automatically tracking the printing of the document file by continuously monitoring and updating a status of the document file to be printed.

Hull et al teaches teach a computer readable medium encoded with a program product, automatically pre-flighting a received document file, including automatically checking for common errors associated during a prepress stage, automatically revising incorrect printing instructions and automatically adding missing printing instructions to the received document file; and automatically providing a remote proofing function for a customer of the document file to be printed and automatically tracking the printing of the document file by continuously monitoring and updating a status of the document file to be printed ("soft-proofing" the job) (page 7, paragraph [0044]).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to have combined the teachings of Stewart with the teaching of Hull to allow a user to "soft-proof" a job to catch any errors in the print job prior to the final output in order to prevent wasting the print jobs resources by having to re-print the job if the errors are not corrected.

Stewart et al and Hull et al fail to teach a computer readable medium encoded with a program product, verifying, at said print service provider location, that said press ready file will print at said print service provider location as designed at the designer location and, if not, correcting said press ready file to ensure printing substantially as

designed; and performing automated shipping using, if created, said corrected press ready file, else using said verified press ready file.

Warmus et al teach a program product, verifying, at said print service provider location, that said press ready file will print at said print service provider location as designed at the designer location and, if not, correcting said press ready file to ensure printing substantially as designed (control unit to control and makeready files and cause one or more demand printing system to print desired pages) (col. 5, lines 44-59); and performing automated shipping using, if created, said corrected press ready file, else using said verified press ready file (printed pages printed by the demand printing system supplied to a finishing apparatus) (col. 5, lines 60-67, col. 6, lines 1-8).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to have combined the teachings of Stewart and Hull with the teaching of Warmus to provide the necessary verification needed to insure the correct output is shipped.

Stewart et al, Hull et al, and Warmus et al fail to teach a program product comprising: establishing a link to the print service provider location from the designer location and obtaining updated device information including functional capabilities of a desired printing device and at least one production device; and verifying that required elements for completion of a production of a print lob at the print service provider location are present in the print job based on the updated device information.

Ryan et al teaches a program product comprising: establishing a link to the print service provider location from the designer location and obtaining updated device

Art Unit: 2625

information including functional capabilities of a desired printing device and at least one production device (Fig. 10 Steps 101) (a table of printer capabilities and constraints is retrieved form the VJTDB and a table of finisher/assembler capabilities and constraints is retrieved form the VJTDB) (col. 18, lines 43-52); and verifying that required elements for completion of a production of a print lob at the print service provider location are present in the print job based on the updated device information (Fig. 10 Step 103) (PMC using the retrieved lists of all of the capabilities and constraints of the devices described in the VJTDB to generate a list of all possible specific paths or threads, by which the retrieved devices can implement the operations and attributes identified in the job model) (col. 18, lines 57-67).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to have combined the teachings of Stewart, Hull, and Warmus with the teaching of Ryan to verify that the printer is capable of outputting the print job prior to submitting the print job to the particular printer.

- 13. Regarding claim 8, Stewart et al teach a program product, wherein said step of creating a press ready file at the designer location further comprises performing automated remote shipping setup of said press ready file to remotely select the desired shipping options for said press ready file when printed at said print service provider location (servicing on the completed jobs includes shipping or delivery of the documents) (col. 8, lines 39-44).
- 14. Regarding Claim 9, Stewart et al teach a program product, wherein said step of verifying, at said print service provider location, further comprises performing automated

remote shipping setup (servicing on the completed jobs includes shipping or delivery of the documents) (col. 8, lines 39-44).

- 15. Regarding Claim 10, Stewart et al teach a program product, wherein said step of automated shipping is performed and wherein an automated shipping device is used to ship said printed output in accordance with shipping instructions in said press ready file (Fig. 7C, S670 and S675, package shrink wrapped and sent for delivery) (col. 9, lines 1-4).
- 16. Regarding Claim 11, Stewart et al disclose a program product, wherein said step of correcting includes reading shipping instructions prepared at the designer location and preparing appropriate corresponding instructions for an actual shipping device to be used at the print service provider location (Fig. 7C, S670 and S675, package shrink wrapped and sent for delivery) (col. 9, lines 1-4).
- 17. Regarding Claim 12, Stewart et al teach a program product, wherein said step of correcting further comprising updating a job ticket corresponding to said press ready file (Fig. 7B, S650 and Fig. 7C, S655, print ready file is transferred to the production facility and gueued to an available printer) (col. 8, lines 62-67, col. 9, lines 1-4).
- 18. Regarding Claim 13, Stewart et al teach a system of managing workflow in a commercial printing environment including a designer location (client side of the network 300a) and a print service provider location (printer side 300c), said system comprising: means for creating a press ready file at the designer location (Fig. 7, S600-640) (user creates a document in a local application, creates a PDF file which is combined with the finishing and binding options to create a print ready file) (col. 8, lines 45-67, col. 9, lines

1-4) using updated device configuration information from the print service provider location (print driver selected by the user is verified) (col. 7, lines 42-67); means for submitting said press ready file to the print service provider location via an electronic network (print ready file is sent to the print queue and transferred to the production facility) (col. 8, lines 45-67, col. 9, lines 1-4).

Stewart et al fails to teach a system comprising: means for automatically preflighting a received document file, including automatically checking for common errors associated during a prepress stage, automatically revising incorrect printing instructions and automatically adding missing printing instructions to the received document file; and means for automatically providing a remote proofing function for a customer of the document file to be printed and automatically tracking the printing of the document file by continuously monitoring and updating a status of the document file to be printed.

Hull et al teaches a system comprising: means for automatically pre-flighting a received document file, including automatically checking for common errors associated during a prepress stage, automatically revising incorrect printing instructions and automatically adding missing printing instructions to the received document file; and means for automatically providing a remote proofing function for a customer of the document file to be printed and automatically tracking the printing of the document file by continuously monitoring and updating a status of the document file to be printed ("soft-proofing" the job) (page 7, paragraph [0044]).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to have combined the teachings of Stewart with the teaching of Hull to

allow a user to "soft-proof" a job to catch any errors in the print job prior to the final output in order to prevent wasting the print jobs resources by having to re-print the job if the errors are not corrected.

Stewart et al and Hull et al fail to teach a system comprising: means for submitting said press ready file to the print service provider location via an electronic network; means for verifying, at said print service provider location, that said press ready file will print at said print service provider location as designed at the designer location and, if not, correcting said press ready file to ensure printing substantially as designed; and means for performing automated shipping using, if created, said corrected press ready file, else using said verified press ready file.

Warmus et al teaches a system comprising: means for submitting said press ready file to the print service provider location via an electronic network; means for verifying, at said print service provider location, that said press ready file will print at said print service provider location as designed at the designer location and, if not, correcting said press ready file to ensure printing substantially as designed (control unit to control and makeready files and cause one or more demand printing system to print desired pages) (col. 5, lines 44-59); and means for performing automated shipping using, if created, said corrected press ready file, else using said verified press ready file(printed pages printed by the demand printing system supplied to a finishing apparatus) (col. 5, lines 60-67, col. 6, lines 1-8).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to have combined the teachings of Stewart and Hull with the

teaching of Warmus to provide the necessary verification needed to insure the correct output is shipped.

Stewart et al, Hull et al, and Warmus et al fail to teach a system comprising: means for establishing a link to the print service provider location from the designer location and obtaining updated device information including functional capabilities of a desired printing device and at least one production device; and means for verifying that required elements for completion of a production of a print lob at the print service provider location are present in the print job based on the updated device information.

Ryan et al teaches a system comprising: means for establishing a link to the print service provider location from the designer location and obtaining updated device information including functional capabilities of a desired printing device and at least one production device (Fig. 10 Steps 101) (a table of printer capabilities and constraints is retrieved form the VJTDB and a table of finisher/assembler capabilities and constraints is retrieved form the VJTDB) (col. 18, lines 43-52); and means for verifying that required elements for completion of a production of a print lob at the print service provider location are present in the print job based on the updated device information (Fig. 10 Step 103) (PMC using the retrieved lists of all of the capabilities and constraints of the devices described in the VJTDB to generate a list of all possible specific paths or threads, by which the retrieved devices can implement the operations and attributes identified in the job model) (col. 18, lines 57-67).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to have combined the teachings of Stewart, Hull, and Warmus with the

teaching of Ryan to verify that the printer is capable of outputting the print job prior to submitting the print job to the particular printer.

- 19. Regarding Claim 14, Stewart et al teaches a method, wherein the required elements present in the print job at the designer location include instructions for shipping (Fig. 7B, S630, user inputs shipping and payment data on the interface) (col. 8, lines 58-60).
- 20. Regarding Claim 15, Stewart et al teaches a method, wherein the press ready file is corrected at the print service provider location by including corrected instructions for shipping (Fig. 7B. S635-640) (shipping and payment data are verified and file is combined with the finishing and binding options to create a print ready file) (col. 8, lines 60-65).
- 21. Regarding Claim 16, Stewart et al teaches a program product, wherein the required elements present in the print job at the designer location include instructions for shipping (Fig. 7B, S630, user inputs shipping and payment data on the interface) (col. 8, lines 58-60).
- 22. Regarding Claim 17, Stewart et al teaches a program product, wherein the press ready file is corrected at the print service provider location by including corrected instructions for shipping (Fig. 7B. S635-640) (shipping and payment data are verified and file is combined with the finishing and binding options to create a print ready file) (col. 8, lines 60-65).
- 23. Regarding Claim 18, Stewart et al teaches a system, wherein the required elements present in the print job at the designer location include instructions for

Art Unit: 2625

shipping (Fig. 7B, S630, user inputs shipping and payment data on the interface) (col. 8, lines 58-60).

24. Regarding Claim 19, Stewart et al teaches a system, wherein the press ready file is corrected at the print service provider location by including corrected instructions for shipping (Fig. 7B. S635-640) (shipping and payment data are verified and file is combined with the finishing and binding options to create a print ready file) (col. 8, lines 60-65).

#### Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to SATWANT K. SINGH whose telephone number is (571)272-7468. The examiner can normally be reached on Monday thru Friday 8am - 4:30pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Edward L. Coles can be reached on (571) 272-7402. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2625

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Edward L. Coles/ Supervisory Patent Examiner, Art Unit 2625 /Satwant K. Singh/ Examiner, Art Unit 2625

sks